

High-Performance Features & Benefits

Crafted for Quality, Designed for Value. Finestra Window & Door features a complete family of vinyl windows and doors.

PREMIER CRAFTSMANSHIP

- Casement Window meets AAMA Grade 50 Performance. See our website for additional performance data
- Smooth operating, weather resistant multi-point locking hardware
- Standard factory mulling
- Color matched folding crank handle
- Pre-punched integral nail fin for easy installation

STRENGTH & INSULATION

- Sealed insulating glass with warm edge metal free insulating glass system maximizes thermal performance and reduces condensation
- Dual compression seal weather stripping for maximum air leak protection
- 4 point fusion-welded corners along with double wall frame provides added strength and insulation



GLASS OPTIONS

Choose from a variety of glass options to meet your aesthetic & performance needs, including Low-E, obscure, tempered, & rain glass. Available configurations include:

- **Simulated Divided Lite (SDL):** 1-1/8"
- **Grids Between the Glass (GBG):** 3/4" flat grids available
- **Insulating Glass (I-G):** 3/4" standard

OPTIONS

- Insect screen available
- WOCD's available
- Egress hinge available
- Field mullion for added flexibility



enviro  sealed
WINDOWS



Ease of Installation & Worry-Free Maintenance

Drywall pass-through window available.

Smooth operating, weather resistant
multi-point locking hardware

Pre-punched integral nail
fin for easy installation

3/4" grids between the glass available

Egress hinge available



Available Frame Colors

Vinyl Colors Available




Laminated Colors Available




Typical Grid Patterns




No Grids



Colonial



Vertical



Perimeter

* The grid patterns shown above are just a small sample of the styles & configurations. Consult your Finestra Window & Door Sales Representative when ordering for a more complete selection of grid styles available.

Thermal Performance

Style	U-Value LoE/Argon Surface #2	U-Value LoE/Argon Surface #2 & #4	R-Value LoE/Argon Surface #2	R-Value LoE/Argon Surface #2 & #4	SHGC No Grids	SHGC with Grids
64 Casement	0.27	0.24	3.70	4.17	0.19	0.17

Structural Performance

Air Infiltration @ 25 mph	0.01 cfm/ft ²
Water Penetration	7.52 psf
Uniform Loads	+ / - 50
Rating	LC - PG 50 - C

