

## High-Performance Features & Benefits

Crafted for Quality, Designed for Value. Finestra Window & Door features a complete family of vinyl windows and doors.

### PREMIER CRAFTSMANSHIP

- Single Slider meets AAMA Grade 30 Performance & above. See our website for additional performance data
- Metal reinforced meeting rail with true interlock system for added strength & security
- Interlocking sweep lock with hidden zinc keeper for added security (passes forced entry test)
- Geometric & architectural shapes
- Standard continuous head and sill factory mulling



### STRENGTH & INSULATION

- Sealed insulating glass with warm edge metal free insulating glass system maximizes thermal performance & reduces condensation
- Dual felt wool pile weather stripping for maximum air leak protection with foam filled bulb seal at bottom of operating sash
- 4 point fusion-welded corners along with double wall frame provides added strength & insulation

### GLASS OPTIONS

Choose from a variety of glass options to meet your aesthetic & performance needs, including Low-E, obscure, tempered, & rain glass. Available configurations include:

- **Simulated Divided Lite (SDL):** 1-1/8"
- **Grids Between the Glass (GBG):** 3/4" flat grids available
- **Insulating Glass (I-G):** 3/4" standard

### OPTIONS

- Insect screen available
- Equal sash 6-0 tall windows available
- Drywall pass-through window available
- 3-lite end vent available



enviro  
sealed  
windows



### Ease of Installation & Worry-Free Maintenance

Drywall pass-through window available.

Lift-out operable sash for easy cleaning

Pre-punched integral nail fin for easy installation

Tandem rollers for easy glide



#### Available Frame Colors


Vinyl Colors Available




Laminated Colors Available




#### Typical Grid Patterns




No Grids



Colonial



Perimeter



Prairie

\* The grid patterns shown above are just a small sample of the styles and configurations. Consult your Finestra Window & Door Sales Representative when ordering for a more complete selection of grid styles available.

#### Thermal Performance

Style	U-Value LoE/Argon Surface #2	U-Value LoE/Argon Surface #2 & #4	R-Value LoE/Argon Surface #2	R-Value LoE/Argon Surface #2 & #4	SHGC No Grids	SHGC with Grids
64 Single Slider	0.27	0.23	3.70	4.35	0.23	0.20

#### Structural Performance

Air Infiltration @ 25 mph	0.08 cfm/ft <sup>2</sup>
Water Penetration	4.50 psf
Uniform Loads	+ / - 45.0
Rating	PG 30 – HS

